

## Single-Step – Direct Print

Product	Width	Printer Compatability	Outdoor Concrete	Indoor Wood	Indoor Tile	Indoor Carpet	Indoor Concrete
Jessup Asphalt Art	48"	UV Curable Only	X		X		X*
Jessup SideWalk	54"	UV Curable Only	X		X		X*
Continental Grafix Walk & Wall	48"	SOL   UV   LTX	X		X	X	X*
Jessup TexWalk	48"	SOL   UV   LTX	X		X	X	X*
Jessup CatWalk	54"	SOL   UV   LTX			X		X*
UltraFlex AdventureScapes	54"	SOL   UV   LTX	X		X	X	X*
Dreamscape Caviar/Ravello	54"	SOL   UV   LTX		X	X		
Speed Vinyl	54"	SOL   UV   LTX	X		X	X	X*
DuraVinyl Single Step	50" & 54"	SOL   UV   LTX			X	X	X*
DuraVinyl 187	54"	SOL   UV   LTX		X	X	X	X

*X\* may leave residue or stain on indoor sealed concrete surfaces*

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## Two-Step – Print & Laminate

Product	Width	Printer Compatability	Outdoor Concrete	Indoor Wood	Indoor Tile	Indoor Carpet	Indoor Concrete
DuraVinyl 253 Removable	54" & 60"	SOL   UV   LTX		X	X		
DuraVinyl 254 Hi-Tack Blockout	54" & 60"	SOL   UV   LTX			X	X	
EcoJet White PVC Free	54" & 60"	UV Curable Only		X	X		
Floor Graphic Bundle: DuraVinyl 203 & InstaShield Floor Guard Economy	54"	SOL   UV   LTX		X	X		
Carpet Graphic Bundle: DuraVinyl 254 & InstaShield Floor Guard Economy	54"	SOL   UV   LTX			X	X	X

Laminates	Width	Thickness	Material	Finish	Indoor Durability	Slip Rating
InstaShield Floor Guard Economy	54" & 60"	3.75 mil	Polyolefin (Non-PVC)	Textured Gloss	90 Days	UL-410
InstaShield FG	54"	5 mil	Semi-Rigid Vinyl	Textured Matte	180 Days	UL-410
Jessup Heavy Duty Overlaminates	54"	23 mil	PVC	Textured Matte	Up to 1 year	ASTM D-2047

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.