

## Asphalt Art by Jessup Manufacturing

**23 Mil Textured PVC | White foil based media  
ASTM D2047 Non-Slip Certified**

### Applications

Asphalt | Concrete | Stone | Brick | Concrete Pillars  
Brick Walls | Smooth and Uneven Surfaces

Tolerates vehicle traffic

### Installation / Removal

Follow recommended installation and removal directions that can be found on the Asphalt Art product page at [qmls.com](http://qmls.com)

## TexWalk by Jessup Manufacturing

**14 Mil Textured PVC - ASTM D2047 Non-Slip Certified**  
**Applications**

Throw away carpet for events/tradeshows

Short term smooth concrete floors

Short term tile floors

### Step One

Print / Trim and apply | Will not shrink

Can be butt seamed

### Removal

Follow recommended removal directions that can be found on the TexWalk product page at [qmls.com/Texwalk](http://qmls.com/Texwalk)

## SportWalk by Jessup Manufacturing

**23 Mil Textured PVC | Waterproof Adhesive**  
**ASTM D2047 Non-Slip Certified**

### Applications

For use on roads, parking lots and sidewalks with heavy pedestrian traffic

Parades | Road Races

### Installation / Removal

Follow recommended installation and removal directions that can be found on the SportWalk product page at [qmls.com](http://qmls.com)



For more information on Jessup's full line of ground graphic products, please visit [www.qmls.com](http://www.qmls.com)

## PRODUCT LINE OVERVIEW

	ASPHALT ART*	TEXWALK*	SPORT WALK*	SOFT WALK*	GLO BRITE*	CAT WALK*	CLEAR WALK*
<b>Compatible Inks</b>	UV & Latex	Solvent, UV, Screen, Latex	Solvent, UV, Screen, Latex	UV	Solvent, UV, Thermal transfer systems	Solvent, UV, Screen, Latex	Solvent, UV, Screen, Latex
<b>Durability</b>	3 to 12 months indoor/outdoor	Up to 3 months on floors indoors; 24-36 months on walls indoors; 1-3 months outdoor on smooth surfaces	Up to 3 week outdoor	Reusable	24-36 months on walls indoors	Up to 3 months indoors	Up to 3 months indoors
<b>Roll Sizes</b>	24" x 10' 48" x 33' 48" x 100'	23" x 10' 48" x 82'	27" x 10' 54" x 33' 54" x 100'	29" x 10' 60" x 82'	27" x 10' 54" x 50' 54" x 150'	27" x 10' 54" x 33' 54" x 100'	27" x 10' 54" x 33' 54" x 100'
<b>Applied Thickness (Substrate &amp; Adhesive)</b>	23 mil	14 mil	23 mil	95 mil (substrate only)	9 mil	20 mil	20 mil
<b>Indoor Use</b>	Exposed brick walls, Smooth and uneven surfaces	Carpet, Tile, Wood, Metal, Sealed concrete, Wall applications on most flat surfaces		Carpet, Tile, Wood, Metal, Smooth concrete	Wall applications or most flat surfaces	Tile, Sealed concrete, Ideal for wet locations around hot tubs, shower stalls and swimming pools	Tile, Sealed concrete, Ideal for wet locations around hot tubs, shower stalls and swimming pools
<b>Tolerates Vehicle Traffic</b>	●						
<b>Outdoor Use</b>	Asphalt, Concrete, Stone, Brick, Concrete pillars, Brick walls	Smooth concrete, Sealed wood	Asphalt, Concrete, Stone, Brick	Asphalt, Concrete, Other smooth surfaces, Floats on water			
<b>100% Recyclable</b>	●						
<b>Repositionable</b>		●		●			
<b>Seam Overlap Ability</b>		●					
<b>Wall Applications</b>	●	●		●	●		
<b>Common Uses</b>	Sports arena, Race tracks, Parades, Retail stores, Marathons, Bike events	Trade show, Retail POP, Wayfinding, Short term outdoor on smooth surfaces	Marathons, Parades, Retail stores, Mall graphics, Canvas prints	POP, events, Trade shows, Pools and Fountains	Events, Safety and promotional signage, Wayfinding, Retail environments	Retail POP, Directional and safety signage	Retail POP, Directional and safety signage
<b>ASTM D-2047</b>	●	●	●	●		●	●
<b>ASTM E84</b>		●					
<b>NFSI Certified</b>	●						

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.