



Instashield Lustre

Instashield Lustre is a neutral finish vinyl film that provides a slight sheen.

Uses

For tradeshow materials and POP displays — indoors or out — Instashield Lustre has proven itself one of the most popular products in the industry for 12 years. It's thicker than many competing films and reduces reflections, while maintaining color contrast, even under heavy display lighting. Its acrylic solvent adhesive also makes it a good choice for outdoor applications.

The QMLS difference

Quality comes first at QMLS. We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size	Catalog #
13" x 150'	0480210
25" x 150'	0480225
38" x 150'	0480237
51" x 150'	0480250
51" x 400'	0480260
54" x 150'	0480270
54" x 400'	0480275
60" x 150'	0480278
61" x 150'	0480279
62" x 150'	0480280

Specifications	
<i>Film</i>	Neutral-finish vinyl
<i>Adhesive</i>	Acrylic solvent
<i>Liner</i>	Paper
<i>Thickness</i>	Film = 3.5 mil Adhesive = 1.2 mil Liner = 78 lb
<i>Processing Range</i>	50° to 120°F
<i>Service Temp Range</i>	-40° to 180°F
<i>UV Protection</i>	UVB Block = 100% UVA Block = 75%
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
<i>Outdoor Durability</i>	2 years
<i>Shelf Life</i>	2 years @ 73° F 50% Relative Humidity

Ordering

Instashield Lustre is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.