



# PromoBond

## Product Description

PromoBond is an ultra-low tac, clear general purpose adhesive that provides great clarity for second surface window applications. The clear solvent removable adhesive can be wet or dry applied. The unique adhesive does not build up over time. When in need of the right mounting adhesive for smooth surfaces, this product provides a clear, distortion free application and allows for a clean, residue free removal.

## Uses

Use PromoBond for mounting to smooth surfaces like glass for a distortion free and cost effective installation.

Applications include:

- Temporary window graphics
- Backlit panels
- General purpose POP

Size	Catalog #
54" x 150'	0477054
60" x 150'	0477060

## Ordering

PromoBond is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

## The Quality Media Difference

Quality comes first at QMLS. We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## Specifications

Carrier	1 mil clear polyester film
Adhesive	Clear permanent solvent adhesive on one side. Clear removable solvent on other side.
Release Liner	Two 1.2 mil clear, polyester
Thickness	Carrier = 1.0 mil Adhesive = 1 mil
Initial Tack	Moderate
Application Temperature	Minimum 50°F
Service Temperature Range	-40° to 180°F
Storage Conditions	50-85°F, 40-80% RH. Store in original packaging.
Shelf Life	One year from ship date when stored in proper conditions.
Outdoor Durability	One year
Winding Orientation	Removable adhesive is wound outside. Permanent adhesive is wound inside.