



HardGuard UV Satin

HardGuard UV Satin

HardGuard UV Satin is a crisp, clear semi-gloss film with a low-melt adhesive system and UV inhibitors.

Uses

For ink jet, plain paper, and photographic prints, HardGuard UV Satin add rigidity and protection from abrasions, moisture, oils, and dirt. It is suitable for single- or double-sided applications, and its satin finish maintains rich, full colors while reducing glare and reflection.

The Quality Media Difference

At Quality Media, we find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to work about waste, reprinting, or relaminating.

Size	Catalog #
12" x 500'	0670500
18" x 500'	0670518
25" x 500'	0670515
38" x 500'	0670525
43" x 500'	0670530
51" x 500'	0670540
55" x 500'	0670560
61" x 500'	0670580

Specifications

Gauge	3.0 mil (10.4 lb) polyester Test method ASTM D645
Primer	2.5 mil (37.1 lb) coextrusion
Yield	9,090 in/lb
Gloss	95, Gardner, 60° Test method ASTM D523
PET Side Coefficient of Friction	0.40 Test method ASTM D1894
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	170° to 245°F
UVA Absorption (315-360 nm)	85% minimum Test method: Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method: Perkin-Elmer Spectrophotometer

Ordering

HardGuard UV Satin is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451