

Quality Value Matte

Quality Value Matte

Quality Value Matte is a 3.5-mil clear flexible intermediate vinyl overlaminate film that is an ideal solution for protecting and enhancing images and graphics.

Uses

Quality Value Matte eliminates reflections and provides a softening effect to color graphics – making it ideally suited for television backdrops and other high-glare applications. Its acrylic solvent adhesive also makes it a good choice for outdoor applications.

The Quality Media Difference

Because we specialize in a large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminatng film you're using are the best possible match – not just for each other, but for the end product.

| Size | Catalog # |
|------------|-----------|
| 38" x 150' | QVLM38150 |
| 51" x 150' | QVLM51150 |
| 51" x 400' | QVLM51400 |
| 54" x 150' | QVLM54150 |
| 61" x 150' | QVLM61150 |

Specifications

| opeonioanione | |
|---------------------------------------|---|
| Film | Matte-finish flexible vinyl |
| Adhesive | Overlaminating permanent solvent |
| Liner | Bleached Glassine |
| Thickness | Film = 3.5 mil Adhesive = 1.2 mil Liner = 50 lb |
| Minimum Application Temperature | 50°F |
| Service Temperature Range | -40°F to + 180°F |
| UV Protection | UVB Block = 100% UVA Block = 75% |
| Chemical Resistance | Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents. |
| Outdoor Durability | 3 years |
| Shelf Life | 2 years at 73°F, 50% relative humidity |

Ordering

Quality Value Matte is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451