



Universal Satin Photo Paper

Universal Satin Photo Paper

Universal Satin Paper has a high opacity base, coated with two ink jet layers to control dot gain and facilitate lamination. Back coated to promote mounting.

Uses

- Indoor Signage
- Posters
- Point of Purchase sales
- Business presentations
- Exhibit and trade show graphics

Size	Gloss Catalog #
24" x 100'	3324
36" x 100'	3336
42" x 100'	3342
50" x 100'	3350
54" x 100'	3354
60" x 100'	3360

Ordering

Universal Satin Photo Paper is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Specifications

Basis Weight	7 mil / 190 grams
Caliper	7.6 mil nominal
Gloss	35 to 55 @ 60 degrees
Opacity	95%
Whitiness	105 minimum
Ink	Dye and pigment compatible
Printing Tips	Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this film, clean and calibrate cartridges before loading the film. While loading the HP 5000 printer only feed 6 inches of paper beyond printer heads. This will prevent alignment errors and banding in printed areas. This media is designed to accept 400% ink loads but increased ink loads will increase dry time. For best results print in 60° to 85°F and 40 to 60% RH.
Finishing Recommendations	This media is not designed for outdoor applications. However, it may be used for outdoor signage if encapsulated on all sides with a UV resistant laminate. Suited for both pressure sensitive and heat activated low temperature laminates. Allow adequate dry times before over laminating.
Shelf Life	2 years
Storage	New rolls = 50° to 86°F. 20-70% relative humidity Open rolls = Cover roll with plastic bag, use end cap if storing on end, do not stack rolls. Allow material to adapt to room conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.