



DSS Pro 14 oz. Blockout



Technical Data Sheet DSS Pro 14 oz. Blockout

DSS Pro 14 oz. Blockout is a two-sided, blockout banner material that is smooth and printable on both sides. The refined scrim pattern and dual print surface were engineered for users seeking a media with a large color gamut at high speeds with low ink consumption. DSS Pro 14 oz. Blockout has a low-curl formula making it ideal for rollup banner stands, POP and indoor hanging graphics. The material is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Available in widths from 39" to 80".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH		
Support Cloth	DIN ISO 2076	Polyester	Polyester		
Yarn dtex	DIN 53830	150 x 150 dtex	150 x 150 denier		
Type of Coating	N/A	PVC	PVC		
Total Weight	DIN EN ISO 2286-2	460 g/m ²	13.5 oz/yd ²		
Tensile Strength	ISO 13934-1:1999 C.R.E. STRIP METHOD	549.4 x 475.0 N/5cm	62.7 X 54.2 lbs/in		
Tear Strength (warp/weft)	ISO 13937-2:2000 C.R.E. SINGLE TONGUE METHOD	13.3 x 6.1 N	2.97 X 1.4 lbs		
Adhesive Strength (warp/weft)	ISO 2411:1991 C.R.E.	4.1 x 4.1 N/5cm	4.68 x 4.68 lbs/in		
Flame Resistance	DIN 75200	NFPA701, Title 19			
Low Temperature (No Crack at:)	ISO 13934:1999	Low at -20°C	Low at -4°F		
RF Weldable (Heat Sealable)	DIN 53354	Yes Yes			
Fungus Resistant	ASTM G21	Yes			

Applications

	POP	Banner	Banner Stands	Block-out	Tradeshow Graphics	Display Systems	Indoor Banners
Applications							

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

Available Sizes

Metric (m)	English (inches)	
0.99, 1.37,	39, 54,	
1.60, 2.03	63, 80	

Information provided here is based on research and is believed to be reliable as of printing date. The information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451