



Strip Mesh Pro LTX



Technical Data Sheet Strip Mesh Pro LTX

Strip Mesh Pro LTX is a 9 oz. mesh with backer that may be easily removed after printing. The specially designed backer creates an air-tight print surface which prevents ink spray through the material. The backer allows vacuum equipped printers to hold material flat during printing. The material is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Strip Mesh Pro LTX allows 25% air-flow through and is ideal for outdoor banners, building wraps, fence mesh graphics and boulevard banners in high wind areas. Available in widths from 54" - 126".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Total Weight	DIN EN ISO 2286-2	305 g/m ²	9 oz/yd ²
Tensile Strength	ISO 13934-1:1999 C.R.E. STRIP METHOD	1917.2 x 1613.2 N/5cm	218.94 x 184.22 lbs/in
Tear Strength (warp/weft)	ISO 13934-1:1999 C.R.E. STRIP METHOD	360.9 x 273.9 N	81.13 X 61.51 lbs/in
Flame Resistance	DIN 75200	NFPA701, B1	
Low Temperature (No Crack at:)	ISO 13934-1:1999	-20 ^o C	-4 ^o F
High Temperature	ISO 13934-1:1999	80 ^o C	176 ^o F
Air Permeability	ISO 9237:1995	1736m ² /sec	

Applications

	Fence Mesh Graphics	Indoor Banners	Boulevard Banners	Outdoor Banners	Building Wrap	Display Systems	Barrier Graphics
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	* ■	■		

Available Sizes

Metric (m)	English (inches)
1.37, 1.52, 1.83, 2.50, 2.64, 3.20	54", 60", 72", 98", 104", 126"

*Certified for HP Latex Inks

Information provided here is based on research and is believed to be reliable as of printing date. The information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451