



Technical Data Sheet
Vulite® Pro BL

Vulite® Pro BL is a 15 oz. economical, back-lit substrate used for a wide array of illuminated indoor or short-term outdoor applications. The smooth print surface has been engineered to avoid flow marks when back-lit. Vulite Pro is available in matte and gloss finishes and is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Available in widths from 54" - 196".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Type of Coating	N / A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	510 g/m ²	15 oz/yd ²
Tensile Strength	ISO 13934-1:1999 C.R.E STRIP METHOD	2065.3 X 1773.0 N/5cm	235.8 X 202.5 lbs/in
Tear Strength (warp/weft)	ISO 13937-2:2000 C.R.E. SINGLE TONGUE METHOD	206 X 167 N	46 X 38 lbs
Flame Resistance	DIN 75200	NFPA701, Title 19, CSFM, B1	
Low Temperature (No Crack at:)	ISO 13934-1:1999	Low at -20°C	Low at -4°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Fungus Resistance	ASTM G21	Treated	

Applications

	Backlit	Banner	Billboard	Blockout	Building Wrap	Display Systems	Truckside
Applications	■	■	■			■	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Available Sizes

Metric (m)	English (inches)
1.37, 2.50, 3.20, 5.00	54, 98, 126, 196

Information provided here is based on research and is believed to be reliable as of printing date. The information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.