



panoRama Clear8020, 7030

A clear, inside mount, self-adhesive perforated window film.

Especially designed for interior applications where city ordinances, tenant agreements, or inclement weather prevent exterior mount window signage.

Available in 80/20 and 70/30 film/open ratios.

APPLICATIONS

- Retail Windows - POP
- Building Wraps
- Rear or Side Bus Windows
- Rear Car Windows
- All Interior Window or Glass Applications

panoRama Clear8020, 7030

MATERIAL

Face Film	Printable Clear Gloss Perforated PVC
Back Side	Clear
Adhesive	Removable Semi-Permanent Clear
Liner	Paper/Polyester Double Liner – 2 mil (50µ +/-10µ)
Film Thickness	6 mil (150µ +/-10µ)
Hole Diameter	1.5 mm
FR Certification	Not Tested

DURABILITY

Interior	Up to 2 years – Vertical Exposure under Normal Conditions
Exterior	Not Applicable
Environment	Humidity & Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 68°F (+15°C to +20°C) and Relative Humidity between 45% to 65%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months – Adhesion May Increase over Time
Removal Temp	+50°F (+10°C) or Greater
Exclusions	+50°F (+10°C) or Greater
Application Advice	NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. For full installation & removal instructions, please refer to "panoRama Clear Perforated Window Film Application & Removal Guide".

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital – UV with White Ink
- Screen Print – Solvent and UV (White Ink Needed)



Material Sizes

- 54" x 100'



Advantages

- NO Lamination Needed – Window Protects the Graphic
- Easy Install on Inside Avoiding Inclement Weather Conditions or Costly Install Equipment
- Available in 80/20 and 70/30 Film/Open Ratios

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

704-872-2216 • www.cgxusa.com