CONTINENTAL



CourtWrap

An ultra-removable polypropylene film with a proprietary repositionable, washable, reusable adhesive.

Use with matched-component CW Protect laminate for a complete floor graphic solution especially designed for smooth athletic playing surfaces.

APPLICATIONS

- Indoor Athletic Court Floors
- Reusable Travel
 Team Logos
- Temporary Dance Floor/Event Graphics



CourtWrap

MATERIAL	
Face Film	Printable White Multilayered Cast Polypropylene
Back Side	Silver Metallic
Adhesive	Proprietary Long-Term Repositionable Removable Reusable – 25g/m2
Liner	Clear PET – 5 mil (125μ +/- 10 μ)
Film Thickness	3 mil (75 μ +/- 10 μ)
FR Certification	Not Tested

DURABILITY	
Interior	Up to 4 Years
Exterior	Up to 3 Years - Vertical Exposure under Normal Conditions
Environment	Humidity and Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Stored at 59°F to 77°F (+15°C to +25°C) with a Relative Humidity between 45% to 70%.
Repositionable	Yes

APPLICATION/REMOVAL +50°F to +86°F (+10°C to +30°C) **Application Temp** +0°F to +122°F (-17°C to +50°C) Service Temp Removability Cleanly Removable with No Adhesive Residue - Adhesion May Increase Depending on Surface and Length of Time Removal Temp +50°F (+10°C) or Greater **Exclusions** NOT to be Applied to PVC, Copper, or Unpainted Metal, as the Application May Become Permanent.

Surface must be clean and dry. Prevent contact with solvent or ammoniabased cleaners. For best results, clean with a mild detergent and water and dry thoroughly. For full installation instructions and tips, please refer to "CourtWrap Application Guidelines."





Printing Methods

- Digital Solvent, Eco-Solvent, UV & Latex
- Screen Print
- Offset



Material Sizes

• 54" x 100'



Advantages

- Easy Application and Removal for Temporary Athletic Floor Graphics
- Washable, Reusable Adhesive Means Graphics May Be Used Again and Again without Loss of Adhesion
- Laminate with Matched-Component CW Protect for Non-Skid Athletic Court Graphics



For additional product information, performance, and warranty guidelines please contact Quality Media and Laminating Solutions. 800-552-9427• www.qmls.com



 $[\]hbox{\it *For critical substrates and all surfaces, please test PRIOR to application.}$