



DuraVinyl 706

Product Description

This 2mil cast gloss white vinyl has a grey opaque adhesive that offers light initial tack for easy repositioning and air release for final positioning. These features are essential for productive vehicle graphic installations. This premium, high performance vinyl is flexible enough to cover any curved or flat surface. Compatible with UV, latex, and eco-solvent inks. Use a premium cast vinyl laminate like Quality Cast Gloss laminate to complete the job.

Uses

- Vehicle wraps - cars, buses, trucks
- Long-term outdoor signage
- Interior brick or block walls

Advantages

- Light tack adhesive allows for easy repositioning of graphic
- 7 year outdoor vinyl
- Compatible with UV, latex and eco-solvent inks

Wrap Film Product Bundle

Product	Size	Catalog #
DuraVinyl 706	54" x 150'	0970654
Premium Cast Gloss Laminate	54" x 150'	0520054
DuraVinyl 706	60"x150'	0970660
Premium Cast Gloss Laminate	60"x150'	0520060

Surface Preparation

All surfaces to which this material will be applied must be thoroughly cleaned with a good quality cleaning solution. Ensure all traces of contamination and cleaning agents are totally removed prior to application of the vinyl. Self-adhesive media should only be applied to OEM painted surfaces and their use on repaired or damaged paintwork is not recommended. The compatibility of lacquers and paints should be tested by the user prior to the application.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

Specifications

Finish	Gloss White
Film Material	2.0 mil cast gloss white
Adhesive	Gray permanent repositionable
Liner	90# polycoated two sides air release liner
Tensile Strength	>2.2lbs / inch
Dimensional Stability	0.02 inch max
Minimum Application Temperature	50°F
Service Temperature Range	-5° to +250°F
Shelf Life	1 year at 73°F, 50% RH
Durability - Unprocessed	10 years - outdoor vertical exposure

Maintenance and Cleaning

Structured films are physically more sensitive than unstructured films and should be treated cautiously. Manual cleaning with a non-abrasive cleaner is recommended. Do not apply wax or polish to the laminated surface. Suggest the use of a medium pressure sprayer. The power sprayer must be perpendicular to the surface. Avoid hitting the edge at an angle with a power spray or it could result in lifting.

Ordering

This wrap film bundle is a Quality Media and Laminating Solutions exclusive bundle. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.