



HardGuard White

HardGuard White

HardGuard White is a white thermal laminating film with low melt adhesive designed for use as a backing film.

Uses

For posters, tradeshow graphics, and POPs where high opacity and flexibility are required, HardGuard White delivers. It offers increased bond strength, consistent quality and when combined with hard-coat thermal laminates, provides a durable end result that won't tunnel or delaminate.

The Quality Media Difference

At Quality Media, we find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to work about waste, reprinting, or relaminating.

5 MIL Size	Catalog #
38" x 250'	0670625
51" x 250'	0670640

10 MIL Size	Catalog #	
38" x 250'	0670835	
51" x 250'	0670850	

Ordering

HardGuard White is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

5 MIL Specifications

Gauge	5 mil
Film	.092 mil polyester
Adhesive	4.08 mil White co-extrusion
Opacity	11% transmission
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Service Temp Range	170° to 245°F
Shelf Life	1 year

10 MIL Specifications

Gauge	10 mil
Film	6.5 mil polyester
Adhesive	3 mil White co-extrusion
Opacity	19% transmission
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Service Temp Range	170° to 245°F
Shelf Life	1 year

Storage

New rolls: 50° to 86°F, 35 to 65% RH.

Open Rolls: Cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

These products are manufactured without the use of CFC's or VOC's.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451