

## SideWalk™

Issue Date: 8/11/2020 - Version 1.2

### DESCRIPTION

SideWalk™ is a 15 mil polyolefin film with a grit texture and a permanent adhesive. The grit surface is rated non-slip by ASTM – D2047 and passes NFSI standards B101.1 and B101.3 for anti-slip. The material is printable with UV, latex and solvent inkjet printers. The acrylic adhesive is ideal for asphalt, concrete, stairs, stone, metal and other walking surfaces.

### APPLICATION

The product is designed for outdoor advertising, way finding, signage, and promotional applications such as sporting events, parades, sidewalks, point-of-purchase, stair and parking lot campaigns, and much more. Equally suitable to handle pedestrian traffic for one day events or long-term applications up to 12 months.

### PROPERTIES

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Thickness	PSTC - 133 - Substrate - Pressure Sensitive adhesive - Release Liner	0.012 inch (0.381 mm) 0.003 inch (0.076 mm) 0.005 inch (0.127 mm)
Peel Adhesion to:  - Stainless Steel	PSTC – 101  15 minute dwell 24 hour dwell	120 oz/in (132 N/100 mm) 175 oz/in (193 N/100 mm)
Shear Adhesion to:  - Stainless Steel	PSTC – 107  1/2” x 1/2” x 1000g	2 hours
Tack	PSTC - 6 Rolling Ball Tack	10+ inches

*\* Color and lot variances of coated surfaces including paints, powder coatings, lacquers, stains, and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface.*



## PROPERTIES

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Wet SCOF	NFSI B101.1	0.91 (min 0.60)
Wet DCOF	NFSI B101.3	0.79 (min 0.45)
Coefficient of Friction (Kinetic)	ASTM D1894	
	Dry Rubber	1.2
	Wet Rubber	1.1
	Dry Leather	0.9
	Wet Leather	1.0

**Note:** While the data contained herein is believed to be reliable averages of the product’s properties, the data should not be used for specification purposes. Jessup Manufacturing Company cannot guarantee colors due to the variation in ink lots, manufacturing processes, etc. Sample colors may also vary as the samples may be shipped from different bundles or lots. Customers who desire specific performance data should contact Jessup Manufacturing Company for further recommendations.

### WARRANTY

Jessup Manufacturing Company products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the Technical Specifications Sheets. Jessup Manufacturing Company will replace or refund the price of any Jessup Manufacturing Company materials found not to meet our product specifications. In no case shall Jessup Manufacturing Company be liable for any direct, indirect, or consequential damages; including labor or non- Jessup Manufacturing Company materials charges.

\*\*The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.