



DreamScape® Specification Sheet

v:030416

Product Names: Silver Flash, Gold Flash, Black Flash, Copper Flash

Description: Printable commercial grade wallcovering media in silver, gold, black and copper . Highly reflective surface. For use in modern wide format inkjet printers.

Construction: Polyester/vinyl face with non-woven backing

Packaging: 3” core, wound print side out, wrapped in black poly-bag, shipped in heavy-duty cardboard tube

Installation: Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

Ink Compatibility: **For UV Curable and HP Latex 3000 series printers**
CAUTION: This product is highly reflective, check with your UV printer manufacturer for their recommendations on printing reflective materials.

Availability: Roll sizes: 54”x25yds, 54”x50yds, 54”x100yds
Trial Rolls (27”x15’)

Weight: Product weight (total): 20oz. Per lineal yd. (13 oz. per Sq. yd.)

Poly/Vinyl weight: 16.8oz. Per lineal yard
Fabric Weight: 2.7oz. Per lineal yard
Adhesive: 0.5oz. Per lineal yard
Thickness: 17 mil.

Type II Properties: Breaking Strength, lbs force
Machine Direction-warp: Exceeds Type II minimum of 50lbs.
Cross Machine Direction-fill: Exceeds Type II minimum of 55lbs.
Tearing Strength, Scale
Machine Direction-warp: Exceeds Type II minimum of 25lbs.
Cross Machine Direction-fill: Exceeds Type II minimum of 25lbs.
Cold Crack Resistance @ 20° F. No Change
Heat Aging (7days at 158° F) Does not become stiff, brittle, discolored or show loss of grain

Specifications: Federal Specification: CCC-408-D Type II WA Specification: W-101 Type II

Fire Testing Methods: ASTM-E84 Tunnel Test Class A

Fire Rating: Meets NFPA Life Safety Code 101 Class A

Mold/Mildew: ASTM-G21 Specifications Passed all requirements

Warranty: 5 Year Warranty against manufacturing defects.

