



# DuraVinyl 355

## DuraVinyl 355

DuraVinyl 355 is a 6.0 mil, non-stretch, white vinyl with permanent solvent adhesive.

## Uses

DuraVinyl 355 is an ideal solution for the following applications:

- Wall graphics
- Window graphics
- Trade show displays
- POP displays
- Mounting to boards
- Pop on site installation

This thick 6 mil vinyl eliminates the need to overlaminate for ease of installation. For ideal results, solvent ink jet printers are recommended. This product is compatible with other printing methods.

## The Quality Media Difference

We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size	Catalog #
54" x 150'	0935554
60" x 150'	0935560

## Specifications

Finish	Matte White
Face Material	6.0 mil semi-rigid vinyl
Adhesive	Permanent Solvent
Liner	90# Polycoated bleached layflat
Minimum Application Temperature	50°F
Service Temperature Range	-40° to +180°F
Shelf Life	1 year
Outdoor Durability	5 years

Target Adhesion Values      15 min.      24 hr.  
(PSTC-1, 180° peel @ 12"/ min., 73° on Stainless Steel)      5.3 lbs./ inch      7.5 lbs./ inch

## Ordering

DuraVinyl 355 is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

**www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451**