



DuraVinyl 456

DuraVinyl 456

DuraVinyl 456 is a flexible 3.1 mil, bubble-free, blockout vinyl with a removable solvent gray adhesive.

Uses

DuraVinyl 456 is an ideal solution for the following applications:

- Trade show displays
- POP displays
- Window graphics
- Flat transit requirements
- Mounting to boards

This flexible vinyl conforms to most wall surfaces and will adhere to eggshell paint surfaces.

For ease of application, a Quality pressure sensitive laminate in recommended. DuraVinyl 400 series is also available with permanent adhesive and gloss white surfaces.

The Quality Media Difference

We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size	Catalog #
30" x 150'	0945630
54" x 150'	0945654
60" x 150'	0945660

Specifications

Finish	Matte White
Face Material	3.0 flexible vinyl
Adhesive	Removable Adhesive
Liner	Air Flow Release Liner
Minimum Application Temperature	50°F
Service Temperature Range	-40° to +180°F
Shelf Life	1 year
Outdoor Durability	5 years

Target Adhesion Values	15 min.	24 hr.
(PSTC-1, 180° peel @ 12"/ min., 73° on Stainless Steel)	25 oz.	32 oz.

Ordering

Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.