



InstaBond C

InstaBond C

InstaBond C is a double-coated polyester film. It has a 1 mil polyester carrier coated on both sides with 1.1 mils of a high tack, moderate peel, moderate shear acrylic adhesive.

Uses

A premier clear carrier film, InstaBond C is used in the graphic arts industry for photo print mounting. InstaBond C makes it easier to view the coated substrate prior to mounting the image – and makes it easier to trim when mounting's completed. The acrylic solvent adhesive performs well in adverse conditions, and the 74 lb liner ensures a smoother end product.

Size	Catalog #
13" x 200'	0470100
25" x 200'	0470117
31" x 200'	0470120
31" x 400'	0470125
38" x 200'	0470137
41" x 200'	0470130
41" x 400'	0470160
43" x 200'	0470150
43" x 400'	0470155
51" x 200'	0470140
51" x 400'	0470170
60" x 200'	0470177
61" x 200'	0470176
62" x 200'	0470175

Specifications

Adhesive	Acrylic solvent, pH neutral
Carrier	1 mil clear polyester
Liner	74 lb matte, stay flat, moisture resistant
Thickness	Liner adhesive = 1.1 mils Exposed adhesive = 1.1 mils Release Liner = 5.1 mils nominal
Processing Range	50° to 120°F
Service Temperature Range	-30°F to 200°F
Peel Adhesion	PSTC #103; backed with 1 mil polyester Exposed side = 40 oz/inch width Liner side = 40 oz/inch width NOTE: Peel tests are performed as per PSTC #103 which states one minute maximum dwell time. In general, longer residence time yields higher peel values.
Static Shear	PSTC #107 Modified; 500 gm/sq inch @ room temp Exposed side = 7+ days Liner side = 7+ days
Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acids and alkalis and many solvents.
Outdoor Durability	2 years
Shelf Life	1 year at 73°F, 50% relative humidity

Ordering

InstaBond C is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.