



InstaShield UV Lustre

InstaShield UV Lustre

InstaShield UV Lustre is a neutral finish vinyl film that provides a slight sheen.

Uses

For tradeshow materials and POP displays – indoors or out — InstaShield Lustre has proven itself one of the most popular products in the industry for 12 years. It's thicker than many competing films and reduces reflections, while maintaining color contrast, even under heavy display lighting. Its acrylic solvent adhesive also makes it a good choice for outdoor applications.

The Quality Media Difference

We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size	Catalog #
25" x 150'	0480225
31" x 150'	0480230
38" x 150'	0480237
41" x 150'	0480240
41" x 400"	0480245
51" x 150'	0480250
54" x 150'	0480270
54" x 400"	0480275
61" x 150'	0480279
62" x 150'	0480280

Specifications

Film	Neutral-finish vinyl
Adhesive	Acrylic solvent
Liner	Paper
Thickness	Film = 3.5 mil Adhesive = 1.2 mil Liner = 78 lb
Processing Range	50°F to 120°F
Service Temperature Range	-40°F to + 180°F
UV Protection	UVB Block = 100% UVA Block = 75%
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents.
Outdoor Durability	3 years
Shelf Life	2 years at 73°F, 50% relative humidity

Ordering

InstaShield UV Lustre is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.