



InstaShield UV Matte

InstaShield UV Matte

InstaShield UV Matte is a top-quality, time-proven, matte finish vinyl film.

Uses

A proven performer, InstaShield Matte eliminates reflections and provides a softening effect to color graphics — making it ideally suited for television backdrops and other high-glare applications. Its acrylic solvent adhesive also makes it a good choice for outdoor applications.

The Quality Media Difference

Because we specialize in a large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminating film you're using are the best possible match — not just for each other, but for the end product.

Size	Catalog #
25" x 150'	0480025
31" x 150'	0480030
38" x 150'	0480037
41" x 150'	0480040
41" x 400'	0480045
51" x 150'	0480050
51" x 400'	0480060
54" x 150'	0480070
54" x 400'	0480080
61" x 150'	0480079

-							70			
v	n	n	n	ifi	0	2	Ť۱	n	n	C
\mathbf{o}	Ш	п	ı.	Ш	ı.	а	ш	ш	ш	
_	r	_	_		_	•		_		•

opecinications				
Film	Matte-finish vinyl			
Adhesive	Acrylic solvent			
Liner	Paper			
Thickness	Film = 3.5 mil Adhesive = 1.2 mil Liner = 78 lb			
Processing Range	50°F to 120°F			
Service Temperature Range	-40°F to + 180°F			
UV Protection	UVB Block = 100% UVA Block = 75%			
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents.			
Outdoor Durability	3 years			
Shelf Life	2 years at 73°F, 50% relative humidity			

Ordering

InstaShield UV Matte is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451