



SuperPrint Plus® FL



Technical Data Sheet

SuperPrint® Plus FL

SuperPrint[®] Plus FL is a 13 oz. front-lit billboard and banner material designed to be the economical alternative to Normandy[®] Pro and JetFlex[®]. The material is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. The face-film provides exceptional ink receptivity and consistently prints from batch to batch. SuperPrint Plus is available in matte and gloss finishes and is available in widths from 38" – 196". The material also comes in 492' rolls specifically engineered for HP Turbojet and screen-printing machines. The rolls are available in 38", 54" and 63" widths and are wound face out on a 6" core.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH	
Support Cloth	DIN60001	Polyester	Polyester	
Yard dtex	DIN60001	1100 x 1100 dtex	1000 x 1000 denier	
Type of Coating	N/A	PVC	PVC	
Total Weight	N/A	440 g/m ²	13 oz.	
Tensile Strength	DIN53352 B53424	1350 x 1200 N/5cm	154.2 x 137lbs/in	
Tear Strength (warp/weft)	DIN53356 B53424	245 x 185 N	55 x 41.6 lbs	
Flame Resistance		NFPA701, B1		
Low Temperature (No Crack at:)	Temperature (No Crack at:) DIN53357		-4°F	
Fungus Resistance	N/A	N/A	N/A	
Puncture Resistance	N/A	N/A	N/A	
RF Weldable (Heat Sealable)		Yes		

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications							

Ink Printability

111111	tability					
Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60,	38, 54, 63
1.83, 2.03, 2.50,	72, 80, 98,
2.60, 3.20, 3.80, 5.00	102, 126, *150, 196

^{*} Matte Finish Only

Information provided here is based on research and is believed to be reliable as of printing date. The information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451