



# Speed Vinyl

## Product Description

Speed Vinyl is a 10 mil promotional-intermediate floor and wall graphic material. 250g nylon fabric reinforced PVC texture vinyl offering anti-slip print surface with high tac but clean removal adhesive.

## Applications

- Finished smooth concrete
- Tile
- Wood
- Other indoor & outdoor mostly smooth surfaces

## Features and Benefits

- Slip resistant: passed UL410 & ANSI\_NFSI B101 standards
- High tac but clean removal adhesive
- Quick and easy production and installation
- 1-step solution (no overlaminates required)
- Mild & Eco Solvent, UVC, GEL and Latex printable.

## Size

54" x 82'

## Catalog #

RSPEEDVINYL-5482

## Installation

Make sure surface is clean and dry. With the adhesive exposed work product onto receiving surface with particular attention to low points. Use Rubber Roller, Felt squeegee or another appropriate applicator. Rounded corners will help avoid edge release. Avoid highly textured surfaces.

## Handling

Avoid touching print surface or introducing dust and dirt on to print face. This can cause anomalies and artifacts when printed. Always store unused material wound tight in original packaging.

## Specifications

Texture & Finish	Matte textured pebble finish with special nylon reinforcement fabric
Adhesive	Solvent/acrylic high-tac with clean removability
Liner	140gsm PE coated silicon paper
Printability	Mild & eco solvent, UVC, GEL and Latex
Minimum Application Temperature	50°F
Durability	Indoor: 3 months to 1 year Outdoor: 1 week to 1 month

## Printing

Suggested Media Setting Universal Self-Adhesive Vinyl. Make sure that ink is dry when it reaches the take-up reel. An external dryer, fan and or heat lamp will accelerate drying.

## Ordering

To place an order for Speed Vinyl, contact your sales representative or call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.