

DuraVinyl 702 | Gloss White with Grayback

Repositionable Adhesive
Air Flow Release Liner | Bubble Free

Applications:

Painted walls | Painted brick and block walls
Vehicle Wraps | Bus Graphics | Fleet Graphics

Part #/ Sizes:

0970254 | 54" x 150'
0970260 | 60" x 150'

Specifications:

Face Material | 2.0 mil vinyl, gray blockout primer
Adhesive | Semi-permanent acrylic (repositionable at application)
Liner | 90# polycoated air flow release liner
Min. Application Temperature | 55°F
Service Temperature Range | -50°F to +225°F
Outdoor Durability | 7 Years
Shelf Life | 2 Years
Recommended Laminate | Quality Premium Cast Laminating Films

DuraVinyl 704 | Gloss White with Grayback

Permanent Hi-Tack Solvent Adhesive

Applications:

Rough Surfaces | Unpainted brick or block walls
Fleet Graphics | Building Wraps | Decals

Part #/ Sizes:

0970454 | 54" x 150'
0970460 | 60" x 150'

Specifications:

Face Material | 2.0 mil vinyl, gray blockout primer
Adhesive | Hi-tack permanent solvent
Liner | 90# polycoated layflat
Min. Application Temperature | 40°F
Service Temperature Range | -50°F to +200°F
Outdoor Durability | 10 Years
Shelf Life | 1 Year
Recommended Laminate | Quality Premium Cast Laminating Films



Visit our website at www.qmls.com for detailed spec sheets on these products.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

Contact us today!

Phone: (800) 552-9427 E-mail: info@qmls.com

Web: www.qmls.com

3/20/2018