

Adhesive Backed Films - 300 Series

DuraVinyl 300 Series are calendared vinyl films specially formulated for digital printing with solvent, UV curable and latex inks. They are offered in gloss white, matte white and clear finishes with permanent, removable and ultra low tack adhesives. DuraVinyl 300 Series is an outstanding choice for a variety of applications including floor / window graphics, trade show / point of purchase displays and wall decals.

5 Mil

DuraVinyl 302

- Gloss White
- Ultra Removable Adhesive
- Applications: Wall Decals, Display Cases/Interior Glass

It is intended to be used as a decal or graphic on most interior flat, smooth and clean surfaces including painted dry wall. It features a semi rigid film that can be printed full bleed and silhouette cut. The micro-sphere adhesive is ultra removable and will remove cleanly for up to 1 year with little/no adhesive residue. When installed to clean surfaces, DuraVinyl 302 can be applied and removed multiple times. To avoid edge curl, always allow 12-24 hours before trimming a full bleed image.

6 Mil

DuraVinyl 305

- Gloss White
- White Pigment Permanent Adhesive
- Applications: Opaque Exterior Window Graphics, Cover-up Decals, Two Sided Windows Indoor Signage, Window, Floor

It can be used for 2 sided window graphics, cover-up labels, decals or other applications where a truly opaque adhesive film is required. DuraVinyl 305 Barrier Film can be used with reverse printed DuraVinyl 262 (clear, dry apply), DuraVinyl 263 (clear, wet apply) or DuraVinyl 463 (clear, dry apply, Air Flow liner) to manufacture interior installed 2 sided window graphics. To avoid edge curl, always allow 12-24 hours before trimming a full bleed image.

DuraVinyl 352

- Matte White
- Ultra Low Tack Adhesive
- Applications: Short Term Interior Window Graphics, Wall Decals

DuraVinyl 355

- Matte White
- Permanent Adhesive
- Applications: POP, Trade Show Graphics, Window Displays



800-552-9427
info@qmls.com
www.qmls.com

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.