

Outdoor Wall Graphics

Quality Media offers a range of solutions for installing outdoor wall graphics for a number of surfaces. Select your substrate and see what products will be compatible with your outdoor wall surface.

Course Plywood

DuraVinyl 435 | Barricade Vinyl*

- Calendared Vinyl | Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Texwalk by JESSUP

- Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
- Outdoor Durability: Up to 1 Year
- Conforms with Surface: Yes
- Widths: 48"

Flat, Painted Plywood

DuraVinyl 435 | Barricade Vinyl*

- Calendared Vinyl | Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Texwalk by JESSUP

- Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
- Outdoor Durability: Up to 1 Year
- Conforms with Surface: Yes
- Widths: 48"

Semi-Gloss, Smooth Plywood

DuraVinyl 454*

- Calendared Vinyl, Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Fabjet II

- Ultra Removable Adhesive backed polyester fabric
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 54" and 60"

Smooth Concrete

DuraVinyl 435 | Barricade Vinyl*

- Calendared Vinyl | Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Texwalk by JESSUP

- Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
- Outdoor Durability: Up to 1 Year
- Conforms with Surface: Yes
- Widths: 48"

Smooth Marble / Granite

DuraVinyl 454*

- Calendared Vinyl, Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Fabjet II

- Ultra Removable Adhesive backed polyester fabric
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 54" and 60"

Slightly Textured Concrete / Stucco

DuraVinyl 454*

- Calendered Vinyl, Semi-Gloss White
- Permanent Adhesive with Smooth Polycoated Liner
- Outdoor Durability: Up to 3 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Fabjet II

- Ultra Removable Adhesive backed polyester fabric
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 54" and 60"

Highly Textured Concrete/ Stucco "Cake Icing"

No Solution Recommended

Unpainted Cinder Block or Brick

DuraVinyl 704**

- 2 Mil Cast Vinyl
- Gray, permanent hi-tack adhesive
- Outdoor Durability: Up to 10 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Texwalk by JESSUP

- Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
- Outdoor Durability: Up to 1 Year
- Conforms with Surface: Yes
- Widths: 48"

Asphalt Art by JESSUP

- Printable, Commerical Grade Slip Resistant White Foiled Based Media
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 48"

Unpainted Cinder Block or Brick

DuraVinyl 702**

- 2 Mil Cast Vinyl
- Gray, bubble-free repositionable adhesive
- Long Term Indoor and Outdoor Walls (Curved and Flat)
- Outdoor Durability: Up to 7 Years
- Conforms to Surface: Yes
- Widths: 54" and 60"

Texwalk by JESSUP

- Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
- Outdoor Durability: Up to 1 Year
- Conforms with Surface: Yes
- Widths: 48"

Asphalt Art by JESSUP

- Printable, Commerical Grade Slip Resistant White Foiled Based Media
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 48"

Fabjet II

- Ultra Removable Adhesive backed polyester fabric
- Outdoor Durability: Up to 2 Years
- Conforms with Surface: Yes
- Widths: 54" and 60"

***Requires Quality Value Laminate | **Requires Quality Premium Cast Laminate**

Application Temp: 60-85 Degrees | Always brush wall first. Remove any adhesive residue.



800-552-9427
info@qmls.com
www.qmls.com

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.