Window Graphics Exterior Mount Solutions

White Printable Films

DuraVinyl 252 | 3.4 Mil

- · Matte White Ultra Low Tack Adhesive
- · Wet or dry installation For Short Term Applications
- Minimum recommended installation: 60°F
- · Laminate recommended

DuraVinyl 352 | 6 Mil

- · Matte White
- · Low Tack Adhesive
- · No laminate required

DuraVinyl 253 | 3.4 Mil

- · Matte White
- · Removable, Medium Tack Adhesive
- · Wet or dry installation to windows
- Laminate recommended

Clear Printable Films

DuraVinyl 262 | 3.5 Mil

- · Gloss Clear
- · Removable Low Tack Adhesive
- · Economical Solution
- · Dry apply to windows

DuraVinyl 263 | 3.5 Mil

- · Gloss Clear
- Removable, Moderate Tack Adhesive
- Will not fog
- · Wet application to windows



Digital Window Graphics (Wincos UV)

- · Optically clear interior window film for use with UV inks
- Clear and distoration free presentation Residue free removal | Available in permanent or removable adhesive
- Scratch Resistant Surface recommended for door installations | UV Protection Available
- · Minimum 1 Year Outdoor Expected Life

Perforated Window Films

ImageVue | 8 Mil

- · Gloss Clear
- · Removable Low Tack Adhesive
- 65/35 Perforated Hole Pattern Premium "retail" vinyl
- · Expected outdoor life up to 3 years

ClassicVue | 8 Mil

- · Matte White Ultra Low Tack Adhesive
- 50/50 perforated hole pattern. Premium "transportation" vinyl
- Expected outdoor life: Up to 3 Years
- · Laminate with Quality Premium Cast Gloss

EconoVue | 8 Mil

- · White Perforated PVC For retail windows, doors, decals
- High Performance Acrylic Adhesive Residue free removal
- Available in 60/40, 70/30,80/20 perforated hole patterns
- 1 Year Outdoor Expected Life

White Adhesive Fabric

Fabjet II

- Ultra Removable Adhesive Backed Polyester Fabric
- Opaque Print Surface Water Resistant and OBA Free
- Compatible with solvent, eco-solvent, UV curable and latex printer | Easy application
- Suitable for outdoor promotional applications on windows, doors, bus shelters, sign boards and other flat surfaces.

