

Quality Media offers a range of solutions for installing outdoor wall graphics for a number of surfaces. Select your substrate and see what products will be compatible with your outdoor wall surface.

Course Plywood

DuraVinyl 435 | Barricade Vinyl *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Texwalk by Jessup

Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
Outdoor Durability: Up to 1 Year | Conforms with Surface: Yes | Widths: 48"



Flat, Painted Plywood

DuraVinyl 435 | Barricade Vinyl *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Texwalk by Jessup

Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes | Widths: 48"

Semi-Gloss, Smooth Plywood

DuraVinyl 454 *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Fabjet II

Ultra Removable Adhesive backed polyester fabric.

Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes | Widths: 54" and 60"

Smooth Concrete

DuraVinyl 435 | Barricade Vinyl *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Texwalk by Jessup

Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes | Widths: 48"

Smooth Marble/ Granite

DuraVinyl 454 *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Fabjet II

Ultra Removable Adhesive backed polyester fabric.

Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes | Widths: 54" and 60"

Contact us today!

Phone: (800) 552-9427 E-mail: info@qmls.com

Web: www.qmls.com

Slightly Textured Concrete/ Stucco

DuraVinyl 454 *

Calendared Vinyl | Semi-Gloss White | Permanent Adhesive with Smooth Polycoated Liner
Outdoor Durability: Up to 3 Years | Conforms to Surface: Yes | Widths: 54" and 60"

Fabjet II

Ultra Removable Adhesive backed polyester fabric.
Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes | Widths: 54" and 60"

Highly Textured Concrete/ Stucco "Cake Icing"

No Solution Recommended

Unpainted Cinder Block or Brick

DuraVinyl 704 **

2 Mil Cast Vinyl | Gray, permanent hi-tack adhesive
Outdoor Durability: Up to 10 Years | Conforms to Surface: Yes
Widths: 54" and 60"

Texwalk by Jessup

Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
Outdoor Durability: Up to 2 Years | Conforms with Surface: No
Widths: 48"

Asphalt Art by Jessup

Printable, Commerical Grade Slip Resistant White Foiled Based Media
Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes
Widths: 48"

Painted Cinder Block or Brick

DuraVinyl 702 **

2 Mil Cast Vinyl | Gray, bubble-free repositionable adhesive
Long Term Indoor and Outdoor Walls (Curved and Flat)
Outdoor Durability: Up to 7 Years | Conforms to Surface: Yes
Widths: 54" and 60"

Texwalk by Jessup

Ultimate One Step Solution for Indoor and Short Term Outdoor Floors and Walls
Outdoor Durability: Up to 2 Years | Conforms with Surface: No
Widths: 48"

Asphalt Art by Jessup

Printable, Commerical Grade Slip Resistant White Foiled Based Media
Outdoor Durability: Up to 2 Years | Conforms with Surface: Yes
Widths: 48"

Fabjet II

Ultra Removable Adhesive backed polyester fabric.

Outdoor Durability: Up to 2 Years | Conforms with Surface: No | Widths: 54" and 60"

*Requires Quality Value Laminate | **Requires Quality Premium Cast Laminate
Application Temp: 60-85 Degrees | Always brush wall first. Remove any adhesive residue.

Contact us today!

Phone: (800) 552-9427 E-mail: info@qmls.com

Web: www.qmls.com

