



AdventureScapes



Technical Data Sheet

AdventureScapes

AdventureScapes is a 100% polyester, anti-microbial, adhesive backed material with an anti-slip embossment. The product is ideal for wayfinding, floor graphics, decals in indoor and outdoor applications. AdventureScapes is tear and wrinkle resistant with an excellent anti-slip rating for wet and dry surfaces. The material does not shrink after printing and is engineered with a quick-drying surface that does not require lamination. AdventureScapes is solvent, eco-solvent, UV & Latex printable. Available in 54" widths.

Material Details

| CHARACTERISTICS | ARACTERISTICS TEST METHOD | | ENGLISH | |
|-----------------------------------|---------------------------|----------------------------------|---------------------|--|
| Material | | 100% Polyester | | |
| Total Thickness | ASTM D645 | 350±10 micron | 0.013 ± 10 in | |
| Total Weight | tal Weight ASTM D645 | | 12.4 oz/ yd² | |
| Whiteness | ISO 105-J02 : 1997 | 70.9 | | |
| Opacity | ISO 2471 : 2008 | > 93.3 | | |
| Surface Finish | | Semi Matte | | |
| Adhesive | | Strong removable | | |
| Released Film | | 100gsm both side PE coated paper | | |
| Slip Resistant DIN 51130: 2014-02 | | Anti-Slip Property | Classification: R11 | |

Applications

| | Floor Graphic | Wallcovering | Decal | Wayfinding | Signage | Outdoor |
|--------------|------------------|--------------|-------|------------|---------|---------|
| Applications | | | | | | |

Ink Printability

| Solvent | Eco Solvent | UV | Latex | Screen Printing | Dye Transfer | Dye Direct |
|---------|----------------|----|-------|--------------------|-----------------|---------------|
| | | | | | | |

Available Sizes

| Metric (m) | English (inches) | |
|------------|------------------|--|
| 1.37 | 54" | |

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451