

Instashield Matte

Instashield Matte is a top-quality, time-proven, matte finish vinyl film.

Uses

A proven performer for over 12 years, Instashield Matte eliminates reflections and provides a softening effect to color graphics — making it ideally suited for television backdrops and other high-glare applications. Its acrylic solvent adhesive also makes it a good choice for outdoor applications.

The QMLS difference

Because we specialize in large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminating film you're using are the best possible match — not just for each other, but for the end product.

S	Size	Catalog #
1	3" x 150'	0480010
2	25" x 150'	0480025
3	38" x 150'	0480037
5	51" x 150'	0480050
5	51" x 400'	0480060
5	54" x 150'	0480070
5	54" x 400'	0480080
6	61" x 150'	0480079

Specifications		
Film	Matte-finish vinyl	
Adhesive	Acrylic solvent	
Liner	Paper	
Thickness	Film = 3.5 mil Adhesive = 1.2 mil Liner = 78 lb	
Processing Range	50° to 120°F	
Service Temp Range	-40 to 180°F	
UV Protection	UVB Block = 100% UVA Block = 75%	
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.	
Outdoor Durability	2 years	
Shelf Life	2 years @ 73°F 50% Relative Humidity	

Ordering

Instashield Matte is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. <u>Click here</u> to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc. 285 State Street, Suite One North Haven, CT 06473 1-800-552-9427 FAX 203 281-6451 info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.