



PolyPerf 7030

Product Description

PolyPerf 7030 is a one-way 100% polyester perforated window film. With a white print-face and laminated dark gray back side, PolyPerf is ideal for interior window mounting. This product has no adhesive. Pair with ViewBond Tape for the perfect interior window solution.

Uses

- Interior second surface mounting to windows, glass, lexan and rollup stands

Benefits

- 100% polyester film (no adhesive)
- Tear resistance, good UV and abrasion resistance
- Eco-Solvent, Mild-Solvent, Screen printability (pretest with Latex)
- 5 year indoor durability under normal conditions
- 70/30 perforation pattern

Size	Catalog #
54" x 41'	875441
54" x 82'	875482
54" x 164'	8754164

Printing

Eco-Solvent

Suggested media setting: Standard Perforated Window Film or PSA Vinyl Setting. Compatible with Screen, Solvent, Eco-Solv. Suggested heater settings 45c-50c. Dry to touch: 5-10 min. An external dryer or heat lamps will accelerate drying.

Latex

Suggested media setting: Generic Polyester.

Handling

Any Perforated material is vulnerable to tunneling due to less surface area adhering to the liner. Handle this product with care and try not to compromise the natural curl. avoid repeatedly bending material. Allow material to adjust to room temperature before printing. rapid temperature swings can cause the liner to tunnel.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

Specifications

Face Material	8 mil PET film
Finish	White print-face
Liner	90# poly-coated bleached layflat
Minimum Application Temperature	50°F
Service Temperature Range	-40°F to +180°F
Shelf Life	1 year at 73F / 50% RH
Outdoor Durability	Up to 7 years

Installation

- Apply ViewBond Tape to the full length of top and bottom edges of the printed side of the graphic
- Clean application surface with isopropyl alcohol
- Using hinge method, temporarily tape the graphic using blue painter tape in position and begin to apply starting at the top
- Flip top of the graphic down from hinge point and remove protective liner from ViewBond Tape
- Flip graphic back up and tack the top edge to the glass starting in center and working out toward left and right edges
- Attach the bottom of the graphic pulling firmly as you apply so there is minimal slack in the graphic

Ordering

PolyPerf 7030 is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.