# LINTEC

# **PVC Free Recycled PET**

# ECO-2306RC

## **PRODUCT DESCRIPTION:**

ECO-2306RC is a 2 mil clear polyester that offers good clarity, dimensional stability, and printability. The polyester face film contains a minimum of 80% recycled post-consumer content. Dry Apply technology incorporates our newest high performance air egress removable acrylic adhesive that offers simple dry installation as well as easy repositionability and removability.


### **TYPICAL APPLICATIONS:**

Advertising and marketing campaigns, point of sale displays, seasonal window graphics, short term promotional campaigns.

### **TYPICAL INDUSTRY SECTORS:**

Retail, restaurants, construction sites, malls, grocery stores.

### **PERFORMANCE:**



**Facestock:** 2 mil clear recycled polyester that offers excellent dimensional stability. The clear polyester provides high resolution imaging with excellent adhesion to UV curable inks.

**Adhesive:** Ultra removable air egress solvent acrylic adhesive. Designed for dry installation and easy removability. Air channels within adhesive allow air to easily escape during dry installation.

**Liner:** 2 sided polyethylene laminated paper with air escape channel technology.

GENERAL CHARACTERISTICS				
Properties	Typical Values Film Adhesive Liner		Unit of Measure   2 mil ± 10%   1 mil ± 10%   7 mil ± 10%	Test Method
Physical				
Peel Adhesion Glass	<b>30 Minutes</b> 3.7	<b>24 Hours</b> 3.7	Newtons @ 72°F , 50% RH	Lintec Method
Visible Light Transmission	90%		Percentage	
Dimensional Stability	Excellent		Inches	FTM 14
Chemical Resistance	3.5 = Good		Grey Scale I = Poor 5 = Excellent	AATCC 8
Minimum Application Temperature	+40°F			
Service Temperature Range	-10°F to +150°F			

The statements in this technical information are based up on our knowledge and practical experience. This data is intended only as a source of information, and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible applications, customers should determine the suitability of this material for their specific purpose prior to use.

LINTEC OF AMERICA, INC.

1292 Barclay Blvd. Buffalo Grove, IL 60089 Tel: 847.229.0547 Fax: 847.229.0548 Toll free: 800.806.8977 www.lintecofamerica.com