



# panoRama CourtWrap/CourtWrap Protect

## Product Description

CourtWrap is a unique print media made of a composite base film and a revolutionary, proprietary, long term repositionable/removable adhesive. The base film is made of a polyester layer to eliminate shrinking and a vinyl layer for ease of printing. CourtWrap is designed for application to smooth, flat surfaces.

## Uses

### Temporary Vehicle Graphics

- Ideal for car dealerships looking for a unique way to promote new vehicle sales on car lots or at events.
- Can be applied to aluminum, steel, plastic and glass surfaces
- Will not scratch paint and will not leave an adhesive residue on the surface.
- No laminate required for this application

### Indoor Athletic Courts

- Ideal for smooth surfaces such as basketball and volleyball courts.
- Must be used with CourtWrap Protect (Textured Non-Slip laminate - ASTM D-2047 and R10 Certified)

### Other Applications:

- Retail Counter Mats
- Tradeshow Graphics

## Advantages

- Easy Installation and removal
- No Adhesive Residue on surface after removal.
- Excellent durability
- Great heat resistance and dimensional stability
- Cleanable Adhesive
- Compatible with Solvent, UV Curable and Latex printers.

Product	Size	Catalog #
CourtWrap	54" x 100'	CGCOURTWRAP-54x100
CourtWrap Protect (Laminate)	54" x 100'	CG COURTWRAP PROTECT-54-100



Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## CourtWrap Specifications

Thickness	8 Mil
Base Film	Polyester/Vinyl Blend
Adhesive	Proprietary, longterm repositionable / removable adhesive
Front	Printable White Surface
Back	Silver Metallic
Liner	135 gsm Siliconized Paper
Printer Compatibility	Solvent, UV Curable, Latex
Cleaning	Dirt and other debris can be washed off the adhesive side with cold water and reapplied to a flat surface.

## CourtWrap Protect Specifications

Thickness	4.7 Mil
Base Film	Textured Vinyl Laminate
Adhesive	Permanent, clear acrylic adhesive
Liner	63 gsm Siliconized Paper
Slip Resistance	ASTM D-2047 and R10 Certified

Humidity and Solvent Resistant	Very Good
Minimum Application Temperature	+50° F to +86°F
Service Range Temperature	+50° F to +86°F
Shelf Life	12 months, stored at +68°F and 50% relative humidity.
Indoor Floor Durability	6-12 months
Indoor Wall and Window Durability	24-36 months
Outdoor window, wall or vehicle durability	6-12 months
Printer Settings	Latex: HP permanent gloss vinyl setting Eco-Solvent: Economy Calendared Vinyl, 35-40° C on pre- and post-heat 720x720 quality  The adhesive is low-tack, so it is very important to minimize the heat used, or you could see tunneling of the liner.

[www.qmls.com](http://www.qmls.com) 800/552-9427 [info@qmls.com](mailto:info@qmls.com) fax 203/281-6451