



NatureWalk

Recyclable polyester textile backed with repositionable, removable adhesive.

Dimensionally stable and tear resistant, NatureWalk is an ideal environmental choice for a wide variety of applications.

The naturally non-skid face film is a great one-step solution for floor graphics or any project where a textured finish is desired.

APPLICATIONS

- Wall and Door Murals
- Museum Exhibits
- Floor Graphics
- Trade Shows

MATERIAL

Face Film	100% Polyester Fabric with a Matte Finish
Back Side	Grey Adhesive
Adhesive	Removable Grey Solvent Acrylic (30μ)
Liner	DPE Coated Paper - 5 mil (133μ +/- 9μ)
Film Thickness	7.5 mil (190μ +/- 30μ)
FR Certification	ASTM E84, M1, B1
Slip Resistance	ANSI A137.1/A326.3, R10

DURABILITY

Interior	Vertical Surfaces - Up to 10 years Flooring Surfaces - Up to 6 Months, Dependent on Traffic
Environment	Humidity & Solvent Resistance - Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 75°F (+ 15°C to +24°C) and Relative Humidity Between 40% and 65%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removal Temp	+50°F (+10°C) or Greater

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean installation surface with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application.

**For critical substrates and all surfaces, please test PRIOR to application.*

Rev 10/2025



Printing Methods

- Digital - Solvent, Eco-Solvent, Latex & UV Inks
- Screen Print



Material Sizes

- 54" x 164'



Advantages

- Leaves No or Almost No Adhesive Residue
- Polyester Film Is Recyclable Where Allowed
- Easy To Apply and Remove
- Print and Go - No Lamination Needed!



For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 • www.cgxusa.com