

# DreamScape™ Specification Sheet

v:091115



<b>Product Name:</b>	<b>DreamScape – 15oz. Type I</b>	
<b>Description:</b>	Digitally printable textured vinyl wallcovering	
<b>Construction:</b>	Vinyl face with non-woven backing	
<b>Packaging:</b>	3” core, wound print side out, wrapped in black back, shipped in heavy duty cardboard tube	
<b>Application:</b>	Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.	
<b>Optimal White Point:</b>	Unprinted white base film should measure no more than 0.5DE from these CieLab values to ensure optimal printing conditions. L* 93.04 a* -0.27 b* -1.42 C* 1.45 h° 259.25.	
<b>Ink Compatibility:</b>	For printers using Solvent, Eco Solvent, UV Curable and Latex	
<b>Availability:</b>	Roll sizes:	54”x25yds, 54”x50yds, 54”x100yds Trial Rolls (27”x15’)
	Textured surfaces:	54” - Matte, Suede, Mystical and Canvas
<b>Weight:</b>	Product weight (total):	15oz. Per lineal yd. ( 10 oz. per Sq. yd.)
	Vinyl weight:	13oz. Per lineal yard, (8oz. Per sq/yd)
	Fabric Weight:	1.5oz. Per lineal yard
	Adhesive:	0.5oz. Per lineal yard
<b>Type I Properties:</b>	<u>Breaking Strength, lbs force</u>	
	Machine Direction-warp:	Exceeds Type I minimum of 40lbs.
	Cross Machine Direction-fill:	Exceeds Type I minimum of 30lbs.
	<u>Tearing Strength, Scale</u>	
	Machine Direction-warp:	Exceeds Type I minimum of 14lbs.
	Cross Machine Direction-fill:	Exceeds Type I minimum of 12lbs.
	<u>Cold Crack Resistance @ 20° F.</u>	No Change
	<u>Heat Aging (7days at 158° F)</u>	Does not become stiff, brittle, discolored or show loss of grain
<b>Specifications:</b>	<u>Federal Specification:</u> CCC-408-D Type I	
	<u>WA Specification:</u> W-101 Type I, NSF/ANSI 342 Sustainability Standard	
<b>Fire Testing Methods:</b>	ASTM-E84 Tunnel Test NFPA 286	
<b>Fire Rating:</b>	Meets NFPA Life Safety Code 101	Class A
<b>Mold/Mildew:</b>	ASTM-G21 Specifications	Passed all requirements
<b>Environmental:</b>	Cadmium and Lead free formulation Prop 65 compliant EU Toxicity – meets all requirements	
	5 Year Warranty against manufacturing defects.	

## Warranty:



800.552.9427 | 203.281.6451 | www.qmls.com