



DuraVinyl 200 Series Adhesive Backed Film

DuraVinyl 200 Series are calendared vinyl films specially formulated for digital printing with solvent, UV curable and latex inks. They are offered in gloss white, matte white and clear finishes with permanent, removable and ultra low tack adhesives. DuraVinyl 200 Series is an outstanding choice for a variety of applications including floor / window graphics, trade show / point of purchase displays and wall decals.

DuraVinyl Calendared Vinyl

A 3 to 5 year outdoor durable calendared vinyl in Gloss White, Matte White or Gloss Clear. Available with permanent, removable or low-tack adhesives and a 90 lb. poly - coated release liner.

Catalog #	Size
DuraVinyl 201 Gloss White, Moderate Tack Perm Adh Applications: POP, Indoor and Outdoor Signage	
0920130	30"x150'
0920154	54"x150'
0920160	60"x150'
DuraVinyl 202 Gloss White, Ultra Low-tack Adhesive Applications: Indoor Wall graphics, POP, Indoor Signage, Window, Floor	
0920230	30"x150'
0920254	54"x150'
0920260	60"x150'
DuraVinyl 205 Gloss White, Hi-Tack Perm Adh Applications: Outdoor Signage, Can be "wet applied"	
0920530	30"x150'
0920554	54"x150'
0920560	60"x150'
DuraVinyl 251 Matte White, Permanent Adhesive Applications: Indoor or Outdoor Signage, POP	
0920130	30"x150'
0920154	54"x150'
0920160	60"x150'
DuraVinyl 252 Matte White, Ultra Low-Tack Adhesive Applications: Indoor Wall Graphics, POP Indoor Signage, Window, Floor	
0925230	30"x150'
0925254	54"x150'
0925260	60"x150'
DuraVinyl 253 Matte White, Removable Adhesive Applications: Outdoor Window Graphics, Floor, Carpet	
0925330	30"x150'
0925354	54"x150'
0925360	60"x150'

Catalog #	Size
DuraVinyl 254 Matte White, Gray Blockout Adhesive Applications: Long Term Signage, POP, Floor, Carpet. Can be "wet applied".	
0925430	30"x150'
0925454	54"x150'
0925460	60"x150'
DuraVinyl 261 Gloss Clear, Permanent Adhesive Applications: Outdoor Signage	
0926130	30"x150'
0926154	54"x150'
0926160	60"x150'
DuraVinyl 262 Gloss Clear, Ultra Low-Tack Adhesive Applications: Interior Window Graphics, Use with Window Cal II	
0926230	30"x150'
0926254	54"x150'
0926260	60"x150'
DuraVinyl 263 Gloss Clear, Low-Tack Adhesive Applications: Interior Window Graphics, Use with Window Cal II Can be "wet applied".	
0926330	30"x150'
0926354	54"x150'
0926360	60"x150'
DuraVinyl 272 Translucent Medium-Tack Removable Adhesive Applications: Interior and Exterior Back-lit Graphics.	
0927230	30" x 150'
0927254	54" x 150'
0927260	60" x 150'

To order call:
(800)552-9427
www.qmls.com
info@qmls.com
fax (203)281-6451



DuraVinyl 200 Series Adhesive Backed Film

Calendared Vinyl

	DuraVinyl 201	DuraVinyl 202	DuraVinyl 205	DuraVinyl 251	DuraVinyl 252
Face Material	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.4 mil flexible vinyl	3.4 mil flexible vinyl
Color/Finish	Gloss white	Gloss white	Gloss white	Matte white	Matte white
Adhesive	Permanent acrylic	Removable acrylic	High tack permanent acrylic	Permanent acrylic	Removable ultra low-tack acrylic
Liner	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat
Min. Appl. Temp	50°F	50°F	50°F	50°F	50°F
Service Temp	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Outdoor Durability	2 years	6 mos avg removability	2 years	2 years	2 years
Shelf Life	2 years	2 years	2 years	2 years	2 years

Calendared Vinyl

	DuraVinyl 253	DuraVinyl 254	DuraVinyl 261	DuraVinyl 262	DuraVinyl 263
Face Material	3.4 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl
Color/Finish	Matte white	Matte white	Gloss clear	Gloss clear	Gloss clear
Adhesive	Medium-tack, removable acrylic	High-tack grey Permanent acrylic	Permanent acrylic	Removable ultra low-tack acrylic	Removable low-tack acrylic
Liner	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	72# high-release Kraft
Min. Appl. Temp	50°F	50°F	50°F	50°F	50°F
Service Temp	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Outdoor Durability	6 mos avg removability	2 years	2 years	6 mos avg removability	3 years
Shelf Life	2 years	2 years	2 years	2 years	2 years

Calendared Vinyl

	DuraVinyl 272
Face Material	3.2-mil flexible translucent vinyl
Color/Finish	White semi-gloss
Adhesive	Medium-tack removable acrylic
Liner	90# polycoated bleached layflat
Min. Appl. Temp	50°F
Service Temp	-40°F to +180°F
Outdoor Durability	5 years
Shelf Life	2 years