



# Budget Banner

## Budget Banner

Budget Banner is designed for short-term outdoor, and low cost indoor, tear resistant banners. This matte polypropylene product will produce outstanding images with all of today's most popular wide format thermal and piezo printers using pigment and dye based aqueous inks. Pigment based aqueous inks are recommended for outdoor applications.

## Uses

- Indoor/outdoor signage (Posters, point of sale)
- Presentations and exhibits
- Indoor/outdoor banners and posters.

Features pigment and dye compatibility, biaxial tear resistance and a superior outdoor coating.

## Finishing Recommendations

This media is designed for indoor and outdoor applications. For prints remaining outdoors for more than three months, overlamine with InstaShield UV Matte or InstaShield UV Lustre is recommended. Allow adequate dry times before overlaminating. No material safety data sheets are required with this product.

Size	Catalog #
36" x 100'	6736
42" x 100'	6742
50" x 100'	6750
60" x 100'	6760

## Ordering

Budget Banner is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## Specifications

Material	Matte Polypropylene
Thickness	7.5 mil
Weight	130 gsm
Color	L* = 93.27, a* = -0.56, b* = -1.47
Whitiness	>130 CEI
Opacity	>90%
Fire Rating	Class A Flame Rating
Core Size	2"
Ink Compatibility	Thermal and piezo inkjet printers using water-based dye and pigmented inks.
Printer Settings	For the best results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. If these tools are not available, printers should be set for the highest print quality and media selection should be "heavy coated". For best results, ink coverage up to 250% is recommended.
Light Fastness	The fading time of inkjet ink is a result of the inks that you choose to use and the environment where the print is displayed.
Finishing	<p>Grommets</p> <ul style="list-style-type: none"> <li>• Place on hemline along the length of the banner so that they go through two layers.</li> <li>• Corner grommets should be placed where the length and width hems intersect, so that it goes through four layers. A reinforced corner can be used to increase durability.</li> </ul> <p>Tape/Stitched Hem</p> <ul style="list-style-type: none"> <li>• 4 Mil Banner tape is recommended over sewing. If sewing, a double-stitched hem is advised with a maximum of five stitches per inch.</li> </ul> <p>Finishing</p> <ul style="list-style-type: none"> <li>• Pressure sensitive vinyl laminates can be used to protect against fade and abrasion of the image. Allow image to dry 24 hours before applying laminate.</li> </ul>
Service Temperature Range	-40-176°F,
Printing Temperature Range	60-80°F, 50% RH
Shelf Life	1 year from ship date
Storage	70°F, 50% RH. Store in original packaging.