



DigiGuard UV Matte

DigiGuard UV Matte

DigiGuard UV Matte features a low-melt adhesive system with a matte finish and UV inhibitors.

Uses

For pop-ups and displays – from ink jet, plain paper, and photographic prints – DigiGuard UV Matte provides the flexibility of single- or double-sided application while eliminating light transference and reflection. It also adds rigidity and protection from abrasions, moisture, oils, and dirt. When images are ink jet printed, our Quality Satin Paper and Ink Jet Coated Media have been specially designed to work with DigiGuard UV Matte for superior end results.

The Quality Media Difference

When you choose Quality Media, you get the convenience of five fully-stocked distribution centers in Connecticut, Florida, Georgia, Minnesota, and Texas – allowing for same-day shipping and next-day shipping on most orders. If your products are ever backordered, we give you the option of choosing an alternative at no additional cost.

| Size | Catalog # |
|------------|-----------|
| 25" x 500' | 0890810 |
| 38" x 500' | 0890825 |
| 43" x 500' | 0890830 |
| 51" x 500' | 0890840 |
| 55" x 500' | 0890860 |
| 62" x 500' | 0890870 |

Specifications

| | |
|----------------------------------|--|
| Gauge | 3.00 mil |
| Film | 0.48 mil polyester |
| Adhesive | 2.50 mil coextrusion |
| Yield | 9,090 in/lb |
| PET Side Coefficient of Friction | 0.40 |
| Heat Seal Initiation Temp | 170°F @ 40psi, 0.5 sec dwell |
| Useable Temp Range | 190° to 245°F |
| UVA Absorption (315-360 nm) | 85% minimum Test method: Perkin-Elmer Spectrophotometer |
| UVB Absorption (260-315 nm) | 100% Test method: Perkin-Elmer Spectrophotometer |

Ordering

DigiGuard UV Matte is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.