



DuraPrint Silver

DuraPrint Silver 5 mil

DuraPrint Silver is a high gloss, 5 mil, silver polyester film for maximum mirror finish, plus antistatic back-coat. This product is water resistant and is coated to accept eco solvent, latex and UV curable inks.

Uses

- Pop-Up and Roll-Up Displays
- POP Displays
- Signage and Advertising

DuraPrint Silver can be mounted to rigid boards (with Megabond C adhesive) for displays or hung for dramatic, eye catching effect.

Advantages

- · High Gloss Mirror Finish
- Water Resistant Solution for Mirror Graphics
- The back-coat of this product has an antistatic coating to reduce issues with printing.

Part #	Name	Size
9950100	DuraPrint Silver 5 Mil	50" x 100'
9960100	DuraPrint Silver 5 Mil	60" x 100'

Ordering

DuraPrint Silver is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Specifications		
Film	Polyester	
Finish	High Gloss Mirror	
Thickness	5 Mil	
Weight	163 gsm	
Application Temperature	50°F to 86°F (10°C to 30°C) 30%-70% RH	
Storage Temperature	41°F to 86°F (5° to 30°C)	
Shelf Life	24 Months	
Outdoor Durability	Indoor Use Only	
Finishing	Use only with Pressure Sensitive Laminates.	
Printing Notes	Compatible with Latex, UVC and silkscreen printers. Compatible with Ecosol, Roland, Mimaki JV3, and Seiko Colorpainter printers. Testing is recommended, as solvent inks can vary widely. UV curable printers- please check users manual to verify that print head can accept "mirror like" media. Always use gloves when handing this product.	
Storage	Always store unused product in original plastic bag.	

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451