

DuraVinyl 187 | Floor Graphics

Snecifications

Product Description

DuraVinyl 187 is an 8 mil, white textured PVC film with a dot pattern pressure sensitive adhesive and a single-sided, siliconized clay coated liner.

Uses

- Short Term Floor Graphics
 - Sealed Wood and Concrete
 - Waxed Vinyl
 - Marble
 - Ceramic Tile
- Short Term Wall Graphics
 - Other Flat Surfaces such as
 - Tradeshow Displays
 - POP Displays
 - Countertops
- Indoor Use Only

Advantages

- Print surface does not need to be laminated and provides a one step solution for short term floor graphics.
- Surface has a R10 slip resistance rating.
- Bubble-free application on smooth surfaces.
- Easy to apply by hand.
- Removable adhesive that does not leave a residue on surface (within first six months)
- Designed to print on solvent, eco solvent, UV curable and latex printers.

Size	Catalog #
54" x 98'	0918754

oheeningarinis		
Thickness	8 mil monomeric PVC	
Finish	Embossed	
Adhesive	Pressure Sensitive Polyacrylate	
Liner	Bleached Clay Coated Kraft	
Fire Rating	B1 Fire Rating	
Application Temperature	41°F	
Service Temperature Range	0°F to 150°F	
Storage Conditions	65°F to 77°F, 65% RH	
Shelf Life	1 Year	
Printing Recommendation	UV and latex inks provide best durability for floor installations. Sol- vent inks should be tested for scuff resistance.	
Installation	Surface must be clean and free of defects. Smooth surface is required for installation.	
Printer Setting	Use Generic Self Adhesive Vinyl print setting. Always store unused roll	

Ordering

DuraVinyl 187 is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

in plastic bag to prevent tunneling

during the printing operation.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451