



# DuraVinyl 352

## DuraVinyl 352

DuraVinyl 352 is a 6.0 mil, semi-rigid, white vinyl with low peel removable/repositionable acrylic adhesive.

## Uses

DuraVinyl 352 is an ideal solution for the following applications:

- Short-term wall graphics
- Wall decals
- Trade show displays
- POP displays

## Advantages

- Compatible with solvent, UV curable and latex printers
- Can be removed from wall up to one year under normal conditions.

## The Quality Media Difference

We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

### Size

60" x 150'

### Catalog #

0935260

## Specifications

Finish	Matte White
Face Material	6.0 mil semi-rigid vinyl
Adhesive	Low peel removable acrylic adhesive
Liner	90# Polycoated bleached layflat
Minimum Application Temperature	50°F
Service Temperature Range	-40° to +180°F
Shelf Life	1 year
Outdoor Durability	5 years

Target Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
<small>(PSTC-1, 180° peel @ 12"/ min., 73° on Stainless Steel)</small>	16 oz.	24 oz.

## Ordering

DuraVinyl 352 is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

**www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451**