



DuraVinyl 302 Wall Graphic Film

DuraVinyl 302 Wall Graphic Film is a 5 mil gloss white film with an ultra removable adhesive. It is intended to be used as a decal or graphic on most interior flat, smooth and clean surfaces including painted dry wall. It features a semi rigid film that can be printed full bleed and silhouette cut. The micro-sphere adhesive is ultra removable and will remove cleanly for up to one year with little or no adhesive residue. When installed to clean surfaces DuraVinyl 302 can be applied and removed multiple times.

Applications:

Ideal for Wall decals, Display cases, Temporary trade show graphics and Interior glass.

Technical Data:

Film	5mil semi-rigid white gloss
Adhesive	Ultra removable micro-sphere, PSTC-1 180° peel 16 oz. to 24 oz. on stainless steel
Liner	90# poly-coated layflat

DuraVinyl 302

Catalog #	Size
0930254	54" x 150'

Printer/ Ink Compatibility:

- This media is compatible with Solvent, Eco Solvent, Latex and UV curable inkjet printers.
- Printing Environment- 60-85°, 40 to 60% relative humidity.
- Printer settings will vary by printer model and ink platform. Heater setting of 45°C on pre-heat, platen and post-heat are a good starting point.
- DuraVinyl 302 Wall Graphic Film can be printed and machine cut to the edge of graphic. Quality recommends at least 24 hours of cure time before laminating and cutting.

Installation:

- Clean the receiving surface thoroughly and allow plenty of time to dry. Do not use chemical cleaners.
- Allow prints that have been rolled one day to lay flat before installation.
- Install prints from the top edge and work down to the bottom. Apply minimal pressure with felt covered squeegee.
- Work out any bubbles with a squeegee from the center out to the edges.
- Minimum Application Temperature 50°F
- Service Temperature Range -40 to 180°F

Durability and Performance Life:

Water Resistance Good

Print Fade The life of the graphic is determine by a number of factors including ink formulation, adequate ink drying and the environment in which the print is displayed. Consult with the ink manufacture to determine the performance life of the ink.

Outdoor Durability Five years for the film.

Removability Removes cleanly for up to one year.

Shelf Life Two years when stored in original packaging at ideal storage conditions (70°F, 50% RH)

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

To order call:
(800)552-9427
www.qmls.com
info@qmls.com
fax **(203)281-6451**