



HardGuard Diamond

HardGuard Diamond

HardGuard Diamond is a 6 mil thermal laminate that features a low melt adhesive system with UV inhibitors and a fine textured surface that is specially designed for pop-up display panels and other trade show graphics.

Uses

For tradeshow graphics and pop-up displays, HardGuard Diamond is the answer. It allows brilliant colors to shine through and has the ability to withstand the rugged environments required for tradeshow graphics and pop-up displays.

Advantages

Scratch resistant, non-reflective surface for graphic enhancement.

Laminate Hard Diamond over paper with either HardGuard White or HardGuard Light Stop for a durable, rollable tradeshow panel.

Size	Catalog #
25" x 250'	0680715
38" x 250'	0680725
51" x 250'	0680750
55" x 250'	0680760
61" x 250'	0680770
76" x 200'	0680790

Specifications

Film	1 mil embossed OPP (Oriented Polypropylene) sandwiched to a 2 mil polyester.
Adhesive	3 mil Polyethylene
UVA Absorption	85% minimum (Test method Perkin-Elmer Spectrometer)
UVB Absorption	100% minimum (Test method Perkin-Elmer Spectrometer)
Finishing	Use with HardGuard White 5 or 10 mil, HardGuard Light Stopper 5, 10 or 15 mil, or any of our other HardGuard or DigiGuard products.
Service Temperature Range	180°F to 230°F Indoor (This is not a laminator setting).
Application Temperature	190° to 205°F
Storage Conditions	50-85°F, 40-80% RH. Store in original packaging.
Shelf Life	One year from ship date when stored in proper conditions.

Ordering

HardGuard Diamond is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451