



InstaShield UV Gloss E

InstaShield UV Gloss E

InstaShield UV Gloss E is a semi-gloss vinyl film that is a lower-cost alternative to InstaShield Gloss.

Uses

For tradeshow materials, POPs, and as a laminate for vinyl banners of short duration, InstaShield Gloss E delivers high quality at an economical cost. It features a thicker face film and release liner than competing products.

The Quality Media Difference

When you choose Quality Media, you get the convenience of five fully-stocked distribution centers in Connecticut, Florida, Georgia, Minnesota, and Texas – allowing for same-day shipping and next-day shipping on most orders. If your products are ever backordered, we give you the option of choosing an alternative at no additional cost.

| Size | Catalog # |
|------------|-----------|
| 25" x 150' | 0481625 |
| 31" x 150' | 0481630 |
| 38" x 150' | 0481637 |
| 41" x 150' | 0481640 |
| 43" x 150' | 0481645 |
| 51" x 150' | 0481650 |
| 51" x 400' | 0481660 |
| 54" x 150' | 0481670 |

Specifications

| | |
|---------------------------|---|
| Film | Vinyl |
| Adhesive | Permanent acrylic emulsion |
| Liner | Paper |
| Thickness | Film = 3.5 mil Adhesive = 1.2 mil Liner = 90 lb |
| Processing Range | 50°F to 120°F |
| Service Temperature Range | -40°F to + 180°F |
| UV Protection | UVB Block = 100% UVA Block = 80% |
| Chemical Resistance | Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents. |
| Outdoor Durability | 2 years when protected from direct exposure to moisture |
| Shelf Life | 2 years at 73°F, 50% relative humidity |

Ordering

InstaShield UV Gloss E is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.