



Instant Dry White Film

Instant Dry White Film

Instant Dry White Film is a fast drying 5 mil white polyester film with a brilliant white gloss finish and outstanding color pop.

Uses

Main uses include tradeshow, retail and other point of purchase displays where the highest print quality is required.

Advantages

The instant dry feature of this product allows for faster turnaround times. It is water resistant and has a high tear resistance. The smooth surface makes it perfect for facemount prints.

Size	Catalog #
36" x 100'	1336
42" x 100'	1342
50" x 100'	1350
60" x 100'	1360

Ordering

Instant Dry White Film is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Specifications	
Basis Weight	180 g/m²
Caliper	5 mil
Ink Compatibility	Epson, Canon, HP
Water Resistant	Yes
Outdoor Durability	Indoor use only
Finishing	Laminate with pressure sensitive laminates like Instashield UV Lustre. Facemount with Viewbond adhesive. Protect prints imaged with dye inks under glass or laminate to increase gas fastness. Allow 24 hours for ink to cure before protecting image. Laminate to extend the life of the print and increase durability.
Printing Tips	Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this media, clean and calibrate cartridges before loading the paper. While loading the HP 5000/5500/6100 printer, only feed 6" of paper beyond print heads. This will prevent alignment errors and banding. For best results, print in 60° to 85° and 40% to 60% RH.
Storage	Storage: New rolls: 50° to 86°F. 20 to 70% RH. Open Rolls: cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451