



InstaShield FG

InstaShield FG

Instashield FG is a 5 mil, low-glare, rigid vinyl film formulated for floor graphics. This product is UL-410 classified for slip resistance. *UL-Classified product: file number MH14249*

Uses

Combined with Duravinyl Matte or Self Adhesive Matte – InstaShield FG creates durable, high-quality floor graphics with a textured finish for protection and slip resistance. It offers an economical alternative to InstaShield Polycarbonate and, unlike some competing products, features an easy-to-use pressure sensitive adhesive. It can also be combined with InstaBond R when creating floor graphics from photos.

Size	Catalog #
25" x 150'	0500225
38" x 150'	0500238
43" x 150'	0500240
51" x 150'	0500250
54" x 150'	0500254

Floor Graphics Instructions

Compatibility	Designed to be applied to smooth, indoor floor surfaces in good condition, including waxed commercial PVC and ceramic tile. This product should not be laminated to any product that contains migrating plasticizers.
Substrate Condition	Floor surface must be clean and dry. Any wax, paints, or coatings on surface must have good adhesion to flooring substrate. Wait 7 days before applying decal to newly painted surface.
Application Instructions	Peel about 1' of release liner from top of graphic. Fold back and crease liner. Position graphic starting with top. Apply firmly using plastic squeegee. After entire graphic is applied, squeegee entire decal, working from center out, to remove air bubbles and ensure good adhesion. Make sure edges are applied well. Do not apply using the wet method.
Maintenance	Wait 24 hours after application before cleaning or waxing floor. To ensure condition of graphic, avoid exposing to heavy equipment traffic.
Cleaning	Clean scuff marks by rubbing with tennis ball. If that does not work, use isopropyl alcohol (nothing stronger).
Removal	Lift one edge of graphic and pull, using short quick strokes.

Specifications

Film	Matte clear scuff resistant semi-rigid vinyl
Adhesive	Permanent acrylic
Liner	Polyester
Thickness	Film = 5 mil Adhesive = 1.2 mil Liner = 1.5 mil
Processing Range	50° to 90°F
Minimum Application Temperature	50°F
Servicable Temp Range	-40° to +180°F
Flammability	Self Extinguishing
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
Outdoor Durability	2 years
Shelf Life	2 years at 73°F, 50% relative humidity

Ordering

InstaShield FG is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.