



# **Quality Cast Laminates**

### **Product Description**

Quality Cast Laminates are high performance, clear cast vinyl films formulated for extended outdoor durability and maximum conformability. Available in 2.0 mil.

#### Uses

When long term outdoor durability required. A choice of three finishes are available, each are backed with a 50 lb poly-coated release liner (Premium Cast Gloss Plus Film features a polyester release liner which yields crystal clear wet out of the adhesive, perfect for use with one way vision materials like Classic View Window Film). These overlaminate films are recommended for use with DuraVinyl 700 Series printable adhesive vinyl. Perfect for applications that require conformability to complex curves or varied surfaces such as vehicle and fleet graphics.

# 2.0 Mil Premium Cast Overlaminates

Size	Catalog #	
Clear Gloss		
48" x 150'	0520048	
54" x 150'	0520054	
60" x 150'	0520060	
Clear Matte		
48" x 150'	0520148	
54" x 150'	0520154	
60" x 150'	0520160	
Clear Lustre		
48" x 150'	0520248	
54" x 150'	0520254	
60" x 150'	0520260	
Gloss Plus		
54" x 150'	0520354	
60" x 150'	0520360	

# **Specifications**

opeenieunene	
Film	Premium Clear Cast Vinyl
Adhesive	Permanent acrylic
Liner	Gloss, Matte, Lustre = Glassine Gloss Plus = Polyester
Thickness	Film = 2.0 mil
Processing Range	50°F to 100°F
Service Temperature Range	-50°F to + 225°F
UV Protection	UVB Block = 100% UVA Block = 80%
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents.
Outdoor Durability	7 years
Shelf Life	2 years at 73°F, 50% relative humidity

# Ordering

Quality Cast Laminates is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451