

# **Quality PolyPro II**

# **Product Description**

Quality PolyPro II is a matte-finish, smooth and opaque, white polypropylene film. It provides an eco-friendly solution for 2-sided printing applications that require a smooth surface.

#### Uses

- Two-sided banners
- Two-sided window displays
- Indoor and short-term outdoor displays
- Tradeshow graphics
- Photo Printing
- POP/Retail Displays

#### **Advantages**

- · Excellent opacity for two-sided printing
- Exceptional tear strength
- Water resistant
- Eco-friendly and recyclable
- Superior lay-flat characteristics
- Superior dimensional stability for color registration
- Combine Quality PolyPro II with one of our removable clear adhesives to create brilliant 2-sided window graphics.
- Compatible with UV curable and latex printers

Part #	Size
61836	36" x 150'
61850	50" x 150'
61854	54" x 150'
61860	60" x 150'

Specifications	
Thickness	8 mil
Ink	UV Curable and Latex
Finish	Can be grommeted or sewn for use as an indoor banner. Double side tape can also be applied to the substrate.
Outdoor Durability	1 year under normal conditions
Printer Suggestions	Use HP White Satin Poster Paper setting with latex printers. Avoid overheating and be certain that material is dry before take up-reel is engaged. For double sided printing on HP Latex printers: When printing first side, use reverse wind-up setting 1 on take-up reel to help compen- sate for any rolls set curl lifting when printing second side.
Handling/Storage	Use gloves when handling product to avoid fingerprints in high ink areas. Store material in original packaging and away from direct sunlight, dust and dirt.
Shelf Life	6 months at 70°F, 50% RH

## Ordering

Quality PolyPro II is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

## www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451