



Quality Value Gloss

UVB Block = 100% UVA Block = 75%

Once applied to substrate, this

product is generally found to be

resistant to water, mild acid, salt,

alkalis, petroleum bases greases,

1 year at 73°F, 50% relative humidity

oils, and aliphatic solvents.

Quality Value Gloss

Quality Value Gloss is a 3.5-mil clear flexible intermediate vinyl overlaminate film. This premium film and adhesive feature a thinner, more economical 50lb liner. Consistent quality vinyl and smooth liner help eliminate silvering associated with most low cost laminates.

Uses

- Tradeshow Displays
- POP Displays
- Window Graphics

The Quality Media Difference

Because we specialize in a large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminating film you're using are the best possible match — not just for each other, but for the end product.

Size	Catalog #	
38" x 150'	QVLG38150	
51" x 150'	QVLG51150	
51" x 400'	QVLG51400	
54" x 150'	QVLG54150	
60" x 150'	QVLG60150	

openious.		
Film	Gloss-finish flexible vinyl	
Adhesive	Permanent acrylic	
Liner	Polycoated bleached layflat	
Thickness	Film = 3.5 mil Adhesive = 1.2 mil Liner = 90 lb	
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to + 180°F	

Ordering

Shelf Life

UV Protection

Chemical

Resistance

Outdoor Durability

Specifications

Quality Value Gloss is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

3 years

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451