



ViewBond

Product Description

ViewBond is an optically clear, double sided mounting adhesive manufactured in a clean room for optical clarity. It features a permanent acrylic adhesive that has an initial moderate tack and builds to an aggressive permanent bond.

Uses

ViewBond is an excellent choice for applications where an optically clear adhesive is required such as; mounting of backlit films to acrylic and other clear or translucent substrates or any application requiring view thru.

The Quality Media Difference

Quality comes first at QMLS. We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size	Catalog #
------	-----------

13" x 150'	0470400
25" x 150'	0470415
31" x 150'	0470420
38" x 150'	0470437
41" x 150'	0470430
41" x 400'	0470460
51" x 150'	0470440
51" x 400'	0470450
54" x 400'	0470455
61" x 150'	0470478
62" x 150'	0470480
72" x 150'	0470499

Specifications

Carrier	1 mil optically clear polyester film
Adhesive	Clear acrylic adhesive
Release Liner	Two 1.5 mil clear, polyester
Thickness	Carrier = 1.0 mil Adhesive =1 mil
Initial Tack	Moderate
Application Temperature	Minimum 40°F
Service Temperature Range	-40° to 275°F
Storage Conditions	50-85°F, 40-80% RH. Store in original packaging.
Outdoor Durability	Not recommended for outdoor applications.
Shelf Life	One year from ship date when stored in proper conditions.

Ordering

ViewBond is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.